

- Produzione media: 900 scatole/ora
- Production moyenne: 900 boîtes/heure
- Producción promedio: 900 cajas/hora
- Average production: 900 boxes/hour
- Durchschnittliche Produktion: 900 Kartons/Std
- Velocità di trasferimento scatola: ~22 mt/min
- Box transfer speed: ~22 mt/min
- Vitesse de transfert de la boîte: ~22 mt/min
- Transportgeschwindigkeit der Kartons: ~22 mt/min
- Velocidad de desplazamiento caja: ~22 mt/min

- Alimentazione pneumatica
  - Pneumatic power supply
  - Alimentation pneumatique
  - Druckluftspeisung
  - Alimentación neumática
  - Consumo aria per ciclo scatola
  - Air consumption cycle box
  - Consommation d'air par cycle boîtes
  - Luftverbrauch pro Kartonzyklus
  - Consumo de aire por ciclo caja
- 6 bar 22 nl


- 🇮🇹 OPTIONALS:
- Ruote con freno
  - Magazzino motorizzato con capacità scatole fino a 270 sc.modello CAR 2001

- 🇬🇧 OPTIONALS:
- Caster wheels for min working table height 750 mm
  - CAR 2001 Motorised box loader with capacity of 270 boxes

- 🇫🇷 OPTIONALS:
- Roues avec frein pour hauteur de travail 750 mm
  - Magasin de caisses vides CAR 2001 avec une capacité de 270 caisses

- 🇩🇪 OPTIONALS:
- Räder mit Feststellbremse
  - Motorisiertes Magazin für bis zu 270 Faltkartons Typ CAR 2001

- 🇪🇸 OPCIONALES:
- Ruedas con freno
  - Almacén motorizado con capacidad hasta 270 Mod. CAR 2001



F 1000		
	MIN	MAX
L	180 mm	400 mm
W	100 mm	400 mm
H	100 mm	500 mm



- Alimentazione: Trifase/Monofase
- Power supply: Three-phase/Single-phase
- Alimentation: Triphasée/Monophasée
- Speisung: Dreiphasig/Einphasig
- Alimentación: Trifásica/Monofásica
- Potenza installata: 0,40 Kw
- Installed power: 0,40 Kw
- Puissance installée: 0,40 Kw
- Eingerichtete Leistung: 0,40 Kw
- Potencia instalada: 0,40 Kw
- Protezione elettrica: IP54
- Electrical protection: IP54
- Protection électrique: IP54
- Stromschutz: IP54
- Protección eléctrica: IP54

- Sistema vuoto Venturi: 25m3/h 700mm HG
- Venturi vacuum unit: 25m3/h 700mm HG
- Groupe de vide Venturi: 25m3/h 700mm HG
- Vakuum Venturi Gruppe: 25m3/h 700mm HG
- Equipo de vacío Venturi : 25m3/h 700mm HG

- Capacità magazzino: 110 scatole
- Box loader unit capacity: 110 boxes
- Capacité magasin (boîtes): 110 boîtes
- Kartonstapel-Einheit Ladungskapazität: 110 Kartons
- Capacidad almacen: 110 cajas

- 🇮🇹 PLC con pannello touch screen
- 🇬🇧 Control panel with Siemens / Omron / Schneider / Allen-Bradley PLC
- 🇫🇷 Panneau de commandes automate PLC
- 🇩🇪 SPS mit Touch-Screen-Panel
- 🇪🇸 PLC con panel de pantalla táctil



- 🇮🇹 Nastratrice GEM B52 per chiusura falde inferiori scatola
- 🇬🇧 Bottom case sealer GEM B52 model to bottom flaps closing
- 🇫🇷 Scotcheuse de fond des caisses GEM B52
- 🇩🇪 Unterbodenverschleißmaschine GEM B52 Model
- 🇪🇸 Precintadora de fondos de cajas GEM B52